

CEILING LOUDSPEAKERS

PCR Rimless Plastic Ceiling Loudspeakers

ABS plastic ceiling loudspeakers for low impedance audio.


PCR 5 & PCR 8

Loudspeaker coil is specially made 16 ohm in order to use more speakers in one chain.


16 ohm allows connect two speakers in parallel and have 8ohm load, or connect even 4 and use system with 4ohm professional audio amplifier or stereo receiver.






FREQUENCY RESPONSE




IMPEDANCE



HORIZONTAL / VERTICAL POLAR DIAGRAMS



— Horizontal / Vertical



	PCR 5	PCR 8
Rated power	25 W (16 Ω)	35 W (16 Ω)
Sensitivity	89 dB (1 W/1 m)	90 dB (1 W/1 m)
Maximum SPL	101dB (Pmax/1 m) at 15694 Hz	105 dB (Pmax/1 m) at 15249 Hz
Frequency response	80 Hz – 20 kHz	60 Hz – 20 kHz
Dispersion at 1000 Hz	120° conical	120° conical
Driver dimensions	5" (130 mm) woofer, 0,5" (13 mm) tweeter, coaxial	8" (200 mm) woofer, 0,5" (13 mm) tweeter, coaxial
Dimensions	ø 200 mm × 70 mm	ø 250 mm × 95 mm
Weight	0.85 kg	1.4 kg
Material	Plastic, Steel grill	Plastic, Steel grill
Colour	White (RAL 9016)	White (RAL 9016)